

526,648

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
13 May 2004 (13.05.2004)



PCT

(10) International Publication Number
WO 2004/039613 A1

- (51) International Patent Classification⁷: **B60F 3/00**
- (21) International Application Number:
PCT/GB2003/004730
- (22) International Filing Date:
1 November 2003 (01.11.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0225493.6 1 November 2002 (01.11.2002) GB
- (71) Applicants (for all designated States except US): **GIBBS TECHNOLOGIES LTD** [GB/GB]; Avenue Road, Nuneaton, Warwickshire CV11 4LY (GB). **GIBBS TECHNOLOGIES LTD** [—/—]; La Motte Chambers, St. Helier, Jersey JE1 1BJ (GB).
- (72) Inventor; and
(75) Inventor/Applicant (for US only): **GIBBS, Alan, Timothy** [NZ/GB]; 28 Albert Bridge House, 127 Albert Bridge Road, London SW11 4DL (GB).
- (74) Agent: **BAIN SMITH, Timothy**; Wickens Manor, Charing, Nr Ashford, Kent, TN27 0DT (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: AMPHIBIOUS VEHICLE SUSPENSION



FWD

(57) Abstract: Suspension for amphibious vehicle. Amphibious vehicle (1) comprises body (3) and retractable road wheels (12,13). At least one wheel suspension (14,15) comprises member (20) having bearing 24 supporting a wheel, member (20) being connected to the body by at least one upper link (28,30), and at least one lower link (34,36); the bearing being ahead of any connection of lower link(s) with the vehicle body. The bearing may also be ahead of any connection of the lower link(s) with the suspension member. A track control arm (40) may be provided. This arrangement may allow engine (4) to be mounted close to rear driveshafts (10), giving suitable weight distribution for a planing vehicle. The arrangement may also be applied to front and/or non-driven wheels (figs. 3, 4). Hydraulic suspension strut (42) may be used to retract the suspension, pivoting around trunnion mount (44); a strut may act as an upper suspension link.

WO 2004/039613 A1



ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

— before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*